



#### TAIZHOU JULI TOOLS CO.,LTD.

ADD:Xuan Men Industrial Estate, Yuhuan, Taizhou, Zhejiang Province, 317608, China Tel:+86-576-87301677/87301678 Fax:+86-576-87301690 Http://www.zuppertools.com E-mail:sales@juli-tools.com















## WE BUILD WITH YOU

What we build can last for years. But what we do can last forever























#### **START FROM THE YEAR OF 1993**

Since the company began from 1993, ZUPPER TOOL has experienced from "made in China" to "Created in China", We has become the leader of battery hydraulic tools in China more than 30 years

We build the tools for plumbing and heating installations last for years, but what we do can last forever. We manufacture best-in-class products by 350 strong highly trained team and sold over 100 countries.

We work continuously to improve the quality, efficiency and safety of our products to meet global market expectations and requirements. Accordingly many of our products are patented and comply with various international standards. ZUPPER products and you, together, WE BUILD.



#### **MORE THAN 30 YEARS OF EXPERIENCE**

### IMPORTANT EVENTS OF ZUPPER TOOLS

From 1993 until now, ZUPPER TOOL has experienced from "made in China" to "Created in China", We has become the leader of hydraulic tools in China more than 30 years

We build the electrical tools and tools for plumbing and heating installation last for years, but what we do can last forever.

1993

Yuhuan Hydraulic Tools Factory was established, which is the predecessor of ZUPPER TOOLS.

2003

JULI moved to a new factory, and entered the period of rapid development and regularization of enterprise development. 2011

"ZUPPER" brand was born, and get Madrid certification

2012

Draft the industry standard of "crimping tool for cables" and "manual cable cutter" 2015

2014

To be Recognized as High and new tech enterprises

Implement 5S site management and production management

2019

Scheme ERP program, set up provincial testing lab

2021

Provincial hidden champions enterprise

2022

ceremony

Parts products gain certificate ZHEJIANG MADE"PIN" National specialized and sophisticated enterprise--"Little giants"

玉工牌工具

1994

"Yugong" brand was recognized as
"China market protection brand"
by China Light Industry Product Quality
Assurance Center


2008

JULI cooperated with Zhejiang University to develop battery 2020

Get the certificate of intellectual property rights







### **CERTIFICATES FOR PRODUCT QUALITY AND MANAGEMENT**



#### **ZUPPER for enhanced safety and optimized standards**

For us, just meeting the standard is not enough, in terms of safety, efficiency and reliability. We are approved by ISO9001, ISO14001, ISO45001 certificates, and CE, UKCA, RoHS by TUV.



#### More than 100 PATENTS

Including intention patent 22 items, Utility model patent 35items. Our highly skilled development team works constrantly on practical and innovative solutions. We designed and developed with safety, efficiency and durability as our core concepts.

#### **ESTB 1993**



## TOP QUALITY FROM PRECISION PRODUCTION

To ensure the stability and high quality of our products, we purchase raw materials and components that guarantee first-class quality. We have more than 300 processing modern equipment; the latest CNC machines guarantee precision manufacturing for all tool components. The most important part is the key parts and processes of the product are completed in the factory to ensure that each product of the world class level.




## TOP QUALITY FROM MULTIPLE DEPTH INSPECTION

We build Precision Hydraulic Tool Research Institute to test raw material and important components, the only one in Zhejiang Province, it includes spectrometer, three coordinate measuring instruments, Keyence 3D scanner, Salt spray tester, profile meter, Image measuring instrument and spring testing and so on.

#### ESTB 1993

## CONTENT


BATTERY POWERED 10-39 PRESS TOOL	
ELECTRICAL POWERED  PRESS TOOL  HAND-OPERATED HYDRAULIC  PRESS TOOL	
BATTERY PUMP 44-45 CORDLESS TUBING CUTTER 46 CORDLESS TUBE EXPANDING TOOL 47	
BATTERY POWERED  AXIAL PRESS TOOL  48-55	
MANUAL TOOL 56-60	
BENDING TOOL 61	
PRESS JAWS 62-70	



11

### BLM-1930 COMPACT EFFICIENCY DURABLE





OLED Display Show Press Cycles, Power, Errors Info

High Performance 18v Li-ion Battery



#### New generation BLM series Brushless motor Battery Powered Press Tool





- Professional tool for the highest demands
- One-hand operation thanks to ergonomic design
- Compact measures with 350° rotatable head, suitable for tight work area
- Brushless motor

with longer life time, more Run-time and maintenance-free

Updated PCB technology
 waterpreef dustrated met

waterproof, dustproof, metal scraps proof

Optional function

bluetooth, pressure sensor and wireless remote controller





MULTI-LAYER COMPOSITE PIPE

















Specifications			
Capacity:	up to 35mm Stainless steel pipe, Copper pipe	Battery:	18V Li-ion 2.0Ah
	up to 40mm Plastic pipe, Multi-layer composite pipe	Battery Charger:	AC 100V-240V 50-60Hz
		Charging Time:	Approx. 40mins
Output:	19kN	Service Interval:	10000cycles
Stroke:	30mm	Weight:	2.1kgs(tool with battery)
Oil capacity:	Approx. 60ml	Tool Size:	409×120×80mm
Pressing cycle time:	2-45		
Pressing cycles/charge:	180cycles (DN 20 Stainless Steel)		
Model No.	Description	Weight (KGS)	Standard Pack
BLM-1930	BLM-1930 Battery Press Tool Kit without jaws	4.6	1set
	18V, 2.0 Ah Li-Ion Batteries	0.3	2pcs
	Charger	0.5	1pc
Accessories	Plastic case	1.7	1pc
	Sealing ring of cylinder:		1set



### **BLM-2430 Battery Powered Press Tool**

- up to 35mm Stainless steel pipe, Copper pipe
- up to 40mm Plastic pipe, Multi-layer composite pipe 24kN Powerful output

MAX press φ35mm stainless steel pipe 2.1KGS Portable and convenient











X PIPE STAINLESS STEEL PIPE






NEW











**TO BE MORE SMART TO BE MORE SLIM** 



- Ergonomic design with light weight, easily work overhead and in tight spaces
- The indicator light, with green indicating completion of press cycle, and red indicating press error or tool malfunction
- Only 2-4S to finish one cycle press
- SERVICE INTERVAL 10000 cycles

All Tools can be Controlled by One Trigger

Anti-slip Handle

**OLED Display** Show Press Cycles, Power, Errors Info

**Battery Lock** 

**High Performance** 18v Li-ion Battery



- up to 35mm Stainless steel pipe, Copper pipe
- up to 40mm Plastic pipe, Multi-layer composite pipe

The ZUPPER SL series with latest technology, updated structure and extended lifetime.It is slim and smart,really a good choice with in-line grip.



350° rotating head

**LED** indicator For illumination

Manual Retract if Need

**LED** indicator For showing tool status, warning

@**=**GP==



COPPER PIPE



STAINLESS STEEL PIPE







<u> </u>			
Capacity:	up to 35mm Stainless steel pipe, Copper pipe	Battery:	18V Li-ion 2.0Ah
	up to 40mm Plastic pipe, Multi-layer composite pipe	Battery Charger:	AC 100V-240V 50-60Hz
Output:	19kN	Charging Time:	Approx. 40mins
Stroke:	30mm	Service Interval:	10000cycles
Oil capacity:	Approx. 35ml	Weight:	2.1kgs(tool with battery
Pressing cycle time:	2-4S	Tool Size:	409×119×76mm
Pressing cycles/charge:	180cycles (DN 20 Stainless Steel)		
Model No.	Description	Weight (KGS)	Standard Pack
SL-1930	SL-1930 Battery Press Tool Kit without jaws	4.6	1set
	18V, 2.0 Ah Li-Ion Batteries	0.3	2pcs
		٥٢	1pc
	Charger	0.5	, po
Accessories	Charger Plastic case	1.7	1pc
Accessories			·





### **SL-2430 Battery Powered Press Tool**

- up to 35mm Stainless steel pipe, Copper pipe
- up to 40mm Plastic pipe, Multi-layer composite pipe 24kN Powerful output

MAX press φ35mm stainless steel pipe 2.3KGS Portable and convenient





COPPER PIPE

MULTI-LAYER COMPOSITE PIF






EX PIPE

STAINLESS STEEL PIPE












# SMALLER, FASTER, LIGHTER COMPACT MEASURES HUGE POWER



#### THE RIGHT TOOL FOR YOUR NEEDS

- CIRCUIT BOARD DIAGNOSTICS Alart you when the battery is low or the tool is too hot or cold
- OLED DISPLAY
- Easy reading on
- Battery Percentage
- Pressing Times
- Fault Code
- Maintenance Note



- 180°SWIVELLING BARREL Easy access to connections
- TWO STAGE HYDRAULIC SYSTEM Hydraulic Ram Output provides more force for reliable connection
- ERGONOMIC DESIGN With light weight and inline grip, easily work overhead and in tight spaces.
- SERVICE INTERVAL: 10000 Cycles



**CIRCUIT BOARD DIAGNOSTICS** Alart you when the battery is low or the tool is too hot or cold

21





#### PZ-1930 **Battery Powered Press Tool**

#### Precise pressing with lighter body

- up to 35mm Stainless steel pipe, Copper pipe
- up to 40mm Plastic pipe, Multi-layer composite pipe

The PZ-1930 is mini press tool with in-line grip, it is efficient and reliable way to join copper, stainless steel and PEX & Multi-layer Pipe.



BATTERY POWERED PRESS TOOL








STAINLESS STEEL PIPE





PER CYCLE TIME



#### PZ-2430 **Battery Powered Press Tool**

24kN Powerful output MAX press \$\phi\$ 35mm stainless steel pipe 2.2KGS Portable and convenient

- Quality guaranteed Core parts are general utilization and standardization
- Ergonomic design With light body
- OLED display shows battery percentage, press cycles, fault code, maintenance note





MULTI-LAYER COMPOSITE PIPE



PEX PIPE















Specifications			
Capacity:	up to 35mm Stainless steel pipe, Copper pipe	Pressing cycles/charge:	180cylces(φ20mm stainless steel pipe)
	up to 40mm Plastic pipe, Multi-layer composite pipe	Battery:	18V 2.0Ah Li-ion
Rated pressure:	24kN	Charging voltage:	AC100-240V 50-60Hz
Rated power:	270W	Charging time:	Approx.40mins
Stroke:	30mm	Service interval:	10000cycles
Pressing cycle time:	2.5-5S	Weight:	3.38kgs(tool with battery and jaw)
		Tool size:	362x122x76mm
Model No.	Description	Weight (KGS)	Standard Pack
PZ-2430	PZ-2430 Battery Press Tool kit without jaws	4.7Kgs	1set
PZ-2430	18V 2.0Ah Li-ion Batteries	0.3Kgs	2pcs
	Charger	0.5Kgs	1pc
Accessories	Plastic case	1.7Kgs	1pc
	Sealing ring		1set



#### **BZ-1930 Battery Powered Press Tool**

improved ergonomic design and huge power in zupper hydraulic system

- Ergonomic designed with 30cm length and 2kgs lightweight, comfortable operation.
- The spare parts are made of high quality aviation aluminum
- Only 4-6S to finish one cycle press
- The tool includes two 18V, 2.0Ah Li-ion and one charger
- It is actuated by motor and controlled by MCU, with two stage hydraulic system.
- SERVICE INTERVAL 10000 cycles





















Capacity:	up to 35mm Stainless steel pipe, Copper pipe	Battery:	18V Li-ion 2.0Ah
	up to 40mm Plastic pipe, Multi-layer composite pipe	Battery Charger:	AC 100V-240V 50-60Hz
		Charging Time:	Approx. 40mins
Output:	19kN	Service Interval:	10000cycles
Stroke:	30mm	Weight:	Approx.2.4kgs (tool with battery)
Oil capacity:	Approx. 60ml		Approx. 3.9kgs(tool with battery and
Pressing Cycle Time:	4-6S	Tool Size:	300×276×75mm
Pressing Cycles/charge:	180cycles (DN 20 Stainless Steel)		
Model No.	Description	Weight (KGS)	Standard Pack
BZ-1930	BZ-1930 Battery Press Tool Kit without jaws	6.20	1set
DZ-1730			
BZ-1730	18V, 2.0Ah Li-Ion Batteries	0.3	2pcs
DZ-1730	18V, 2.0Ah Li-Ion Batteries Charger	0.3	2pcs 1pc
			•
ACCESSORIES	Charger	0.5	1pc



25





## PZ-3240 Battery Powered Press Tool THE MOST DURABLE

#### THE MOST DURABLE INTELLIGENT PRESS TOOL

V LONGER WARRANTY

2years or 40000cycles

**BATTERY POWERED PRESS TOOL** 

**☑** OPTIONAL EXTENDED FUNCTIONS

Brushless motor / Pressure sensor / Bluetooth

180° SWIVELLING BARREL Easy access to connections

Press cycle, Version Number,
Maintenance note,
Battery percentage, Fault code
Rest available press cycles before
next maintenance

All tools can be controlled
by one trigger

LED Light

Manual Retract

High Performance 18V Li-ion Battery

High Performance 18V Li-ion Battery









CUDDED DID

MULTI-LAYER COMPOSITE PIPE

PEX PIPE

STAINLESS STEEL PIPE

Specifications			
Capacity:	up to 54mm Stainless steel pipe	Pressing cycles/charge:	350cycles(DN 20 Stainless Steel)
	up to 108mm Plastic, Multi-layer composite	Battery:	18V Li-ion 4.0Ah
	and Copper pipes	Charging time:	Approx.80mins
Output:	32kN	Charging voltage:	AC 100V-240V 50-60Hz
Stroke:	40mm	Service interval:	10000cycles
Pressing cycle time:	3-6s(depends on the dia of pipe)	Weight:	4.1kgs(tool with battery)
Tool Size:	495x89x123mm		6.2kgs(tool with battery and jaw)

### **ED-5050 Battery Powered Press Tool**

For thick stainless steel, copper

- Designed with matching press jaws
- Cylinder is made of steel, Longer span life
- Two stage hydraulic system, high-efficiency
- OLED Display shows battery percentage, pressing times, fault code, maintenance note.

#### PZ-5050 Battery Powered Press Tool

For thick stainless steel, copper

- Cylinder is made of high strength steel,longer span life
- Aerometal ram with matching press jaws, suit for thick pipe connections
- New design conform to ergonomics and optimized position of centre of gravity
- 180° swivelling barresl,easy access to connections
- Warranty 2years or 30,000cycles
- Brushless motor is optional, suit for inflammable and explosive field(professional test before using)
- Pressure sensor and Bluetooth wireless communication technology is optional







Specifications	ED-5050	PZ-5050
Capacity:	up to 54mm Stainless steel pipe	up to 54mm Stainless steel pipe
	up to 108mm Plastic, Multi-layer composite and Copper pipes	up to 108mm Plastic, Multi-layer composite and Copper pipes
Rated pressure:	50kN	50kN
Stroke:	50mm	50mm
Time/work:	3-6s(depend on the dia of pipe)	3-6s(depend on the dia of pipe)
Cycles/charger:	180cycles	180cycles
Battery:	18V Li-ion 4.0Ah	18V Li-ion 4.0Ah
Charging voltage:	AC 100V-240V 50-60Hz	AC 100V-240V 50-60Hz
Charging time:	Approx.80mins	Approx.80mins
Service Interval:	10000cycles	10000cycles
Weight:	4.7kgs(with battery)	4.9kgs(with battery)

Battery Press Tool Kit				
	ED-5050	Weight(kgs)	PZ-5050	Weight(kgs)
	Battery, 18V, 4.0Ah Li-Ion	0.6kgs	Battery, 18V, 4.0Ah Li-Ion	0.6kgs
ACCESSORRIES	Charger	0.5kgs	Charger	0.5kgs
	Plastic case	4.1kgs	Plastic case	4.1kgs





- Battery press tool with in-line grip.Only 3-4.5S to finish one cycle press
- The tool comes standard with two 18v,4.0Ah Lion-batteries and one charger. It can achieve over 350 cycles per charger.
- Motor drivers, Micro-computer control system, OLED screen and double valve hydraulic system.




















Specificat	ions		
Capacity:	up to 54mm Stainless steel pipe	Battery:	18V Li-ion 4.0Ah
	up to 108mm Plastic, Multi-layer composite	Battery Charger:	AC 100-240V
	and Copper pipes	Charging Time:	Approx. 80mins
Output:	32kN	Service Interval:	10000cycles
Stroke:	40mm	Weight:	Approx.3.9kgs (tool with battery)
Cycle Time:	Approx. 3-4.5 seconds		Approx.6.1kgs(tool with battery and jaw)
Oil capacity:	115ml	Tool Size:	466×126×82mm
P7-1550 R	attery Press Tool Kit		

1 2-1330 Battery 1 1633 100t Nit		
MODEL NO.	DESCRIPTION	Weight(kgs)
PZ-1550	PZ-1550 Battery Press Tool Kit without jaws	9.20
1 2-1330	Battery, 18V, 4.0Ah Li-lon	0.60
ACCESSORRIES	Charger	0.50
ACCESSONNIES	Plastic case	4.20






## POWERFUL, RELIABLE AND SIMPLY PRACTICAL





#### THE RIGHT TOOL FOR YOUR NEEDS

- OLED Data Display to show crimping time, Electricity Quantity, maintenance reminding and fault code.
- Air Cooling Heat dissipation System to extend using life.
- Press head rotates 310°
- Two stage hydraulic system with fast feed and power control
- Quick motor stop guarantees highest safety for the operator
- Automatic retraction when crimp is completed
- Electronic control and monitor of crimping operation
- Ergonomic design and optimized position of centre of gravity



HIGH PERFORMANCE 18V Li-ion Battery

TWO STAGE HYDRAULIC SYSTEM

MANUAL RETRACT IF NEED

ALL TOOLS CAN BE CONTROLLED BY ONE TRIGGER

**OLED DISPLAY** 



CIRCUIT BOARD DIAGNOSTICS Alart you when the battery is low or the tool is too hot or cold





## **ED-1550 Battery Powered Press Tool**

#### Faster & Reliable

The ED-1550 gives another option for a fast and reliable way to join copper, stainless steel and PEX pipe. The tool comes standard with two 18V, 4.0Ah Liion batteries and one charger, motor drives, Microcomputer control system, OLED screen and double valve hydraulic system, it can achieve over 350 cycles per charge.





MULTI-LAYER COMPOSITE





DEY DIDE

STAINLESS STEEL PIPE



3.8s



Specificat	ions			
Capacity:	up to 54mm Stainless s	teel pipe	Battery:	18V Li-ion 4.0Ah
	up to 108mm Plastic,M	ulti-layer composite	Battery Charger:	AC 100-240V
	and Copper pipes		Charging Time:	Approx. 80mins
Output:	32kN		Service Interval:	10000cycles
Stroke:	40mm		Weight:	Approx.3.8kgs (tool with battery)
Cycle Time:	Approx. 3-8 seconds			Approx.6.0kgs(tool with battery and ja
Oil capacity:	115ml		Tool Size:	394×326×84mm
ED-1550 E	Battery Press Too	ol Kit		
MODEL NO.		DESCRIPTION		Weight(kgs)
ED-1550 Bat		ED-1550 Battery Press To	ol Kit without jaws	9.0
ED-1550		Battery, 18V, 4.0Ah Li-lon		0.6
ACCECCODDII	-c	Charger		0.5
ACCESSORRIE	:5	Plastic case		4.1



## HH-60100 Electrical Powered Press Tool For big size from 60-108mm

stainless steel pipe

- Designed with matching press jaws
- Cylinder is made of steel, Longer span life
- Two stage hydraulic system, high-efficiency
- OLED Display shows battery percentage, pressing times, fault code, maintenance note.

## ED-60100 Battery Powered Press Tool For big size from 60-108mm


stainless steel pipe

- Designed with matching press jaws
- Cylinder is made of steel, Longer span life
- Two stage hydraulic system, high-efficiency
- OLED Display shows battery percentage, pressing times, fault code, maintenance note.



Specifications	HH-60100	ED-60100		
Capacity:	up to 108mm St	up to 108mm Stainless steel pipe and Copper pipe		
Rated pressure:	65kN	65kN		
Stroke:	80mm	80mm		
Time/work:	10-25s(depend on the dia of pipe)	10-25s(depend on the dia of pipe)		
Cycles/charger:		50cycles		
Battery:		18V/5.0Ah		
Battery Charger:		AC 100V-240V;50-60Hz		
Charging Time:		Approx.100mins		
Service Interval:	10,000cycles	10,000cycles		
Weight:				

Battery Press Tool Kit					
	HH-60100	Weight(kgs)	ED-60100	Weight(kgs)	
ACCESSORRIES			Battery, 18V, 5.0Ah Li-lon	0.6	
			Charger	0.5	
	Plastic case	6.1	Plastic case	6.1	



35

## NEW TECHNOLOGY OF EB SERIES BRUSHLESS MOTOR

No carbon brush, durability and reliability



#### **BRUSHLESS MOTORS ARE DRIVING REVOLUTIONARY PERFORMANCE**



LONGER **MOTOR LIFE** Longer life and maintenance-free thanks

to brushless technology

MORE **POWER** 

No carbon brush. When the motor is running, there is no power loss by friction and reduce the heat generated by the motor.

**RUN-TIME** Heat generated by Brushless motor is small Compared to the brush motor, the brushless motor will do more work in the same full

+30%

**MORE** 

charge of the battery pack



**APPLICATION** 

No carbon brush, the motor does not produce sparks at work, it is more suitable used in combustible place



#### EB-1550 EB-32100 **Battery Powered Press Tool New Technology Brushless Motor**

- 3-6S to finish one cycle
- Automatic retraction when press is completed
- Two stage hydraulic system
- An ergonomic design and optimized position of center of gravity to provide increased feel and usability
- Micro computer control system



#### **Bluetooth And Pressure Sensor**

Thanks to new implemented Bluetooth technology, devicerelated data can be requested via the ZUPPER APP. The ZUPPER EB Series include BLUETOOTH asbasic configuration, you can choose pressure sensor at optional.

#### **ZUPPER Check-APP**

- Data transfer between press tool and APP
- See the location of where your ZUPPER Link enabled tool was
- Check the pressure by pressure sensor to differentiate the pressure normal or not.
- APP shows the pressure data counter to check and analyze



Technical Data	EB-1550	EB-32100
Capacity:	up to 54mm Stainless steel pipe	up to 54mm Stainless steel pipe
	up to 108mm Plastic, Multi-layer composite and Copper pipes	up to 108mm Plastic, Multi-layer composite and Copper pipes
Output:	32kN	32kN
Stroke:	40mm	40/60/100mm(adjustable)
Cycle time:	3-6s(depands on diameter of pipe)	3-6s(depands on diameter of pipe)
Oil capacity:	115ml	250ml
Pressing cycles/charge	360cycles(DN20 stainless steel)	360cycles(DN20 stainless steel)
Battery:	18V Li-ion 4.0Ah	18V Li-ion 4.0Ah
Charger:	AC 100V-240V 50-60Hz	AC 100V-240V 50-60Hz
Charging time:	Approx.80mins	Approx.80mins
Service Interval:	10000cycles	10000cycles
Weight:	3.8kgs(tool with battery)	
	6.0kgs(tool with battery and jaw)	
Tool Size:	400x318x86mm	525x318x86mm

	EB-1550	Weight(kgs)	EB-32100	Weight(kgs)
	Battery Press Tool Kit without jaws:	9.0	Battery Press Tool Kit without jaws:	
Accessories:	18V Li-ion 4.0Ah	0.6	18V Li-ion 4.0Ah	0.6
Accessories:	Charger	0.5	Charger	0.5
	Plastic case	4.1	Plastic case	4.1

Kit includes: EB-1550 battery press tool, Two 4.0Ah Batteries, One Charger and Carrying case



#### **BZ-1550 Battery Powered Press Tool** 220V Lasting Power Supply High performance, Save time

- Battery press tool with gun type grip.Jaws are made of high strength forging steel.
- LED light for low or no-light environment
- LCD data display can show pressing times, electricity quantity and maintenance reminding information
- The tool comes standard with two 18v,4.0Ah Lion-batteries and one charger. It can achieve over 300 cycles per charger.
- Motor drivers, Micro-computer control system, and double valve hydraulic system.







STAINLESS STEEL PIPE





Specifications				
Capacity:	up to 54mm S	Stainless steel pipe	Battery:	18V Li-ion 4.0Ah
	up to 108mm	Plastic, Multi-layer composite and	Charger:	AC 100V-240V 50-60Hz
	Copper pipes	i	Charging time:	Approx.80mins
Output:	32kN		Service Interval:	10000cycles
Stroke:	40mm		Weight:	4.5kgs(tool with battery)
Cycle time:	3-6s(depands on diameter of pipe)			6.7kgs(tool with battery and jaw)
Pressing cycles/charge	350cycles(DN	V20 stainless steel)	Tool Size:	375x329x85mm
Accessories:				
MODEL NO.		DESCRIPTION		Weight(kgs)
BZ-1550		BZ-1550 Battery Press Too	BZ-1550 Battery Press Tool Kit without jaws	
		18V Li-ion 4.0Ah		0.6
ACCESSORRIES		Charger		0.5
		Plastic case		

Kit includes: BZ-1550 Press Tool, Two 4.0Ah batteries, One charger and carrying case

HIGH PERFORMANCE

SYSTEM UPGRADE, RETRACT STOP FOR

**EFFICIENCY AND SAVE TIME ON EVERY JOB.** 

**POSITION CONTROL.** 






#### MP-1930 Battery Powered Mechanical Press Tool

- up to 35mm Stainless steel pipe, Copper pipe
- up to 40mm Plastic pipe, Multi-layer composite pipe

The MP-1930 is the newest addition of press tool with mechanical system, it is faster and efficient way to join metal pipe and plastic pipe

- The tool is easier to do maintenance
- Enclosed screw structure prevents sand and dust
- Brushless motor with longer motor life and more Run-time
- Screw Drive with high efficient, press more fast
- Ergonomic design, comfortable operation
- ONE KEY control switch, automatically completes press cycles
- The indicator light, with green indicating completion of press cycle, and red indicating press error or tool malfunction





STAINLESS STEEL PIPE









Specifications				
Capacity:	up to 35mm Stainless steel pipe, Copper pipe	Battery:	18V Li-ion	2.0Ah
	up to 40mm Plastic pipe, Multi-layer composite pipe	Battery Charger:	AC 100V-2	40V 50-60Hz
Output:	19kN	Charging Time:	Approx. 40	mins
Stroke:	30mm	Weight:	Approx.2.4	kgs (tool with battery)
Pressing Cycle Time:	2S	Tool Size:	400x119x7	6mm
Model No.	Description	V	Veight (KGS)	Standard Pack
14D 4000	MD 1000 D II D T 11/1 11	4.5	/ 0	4 .

Model No.	Description	Weight (KGS)	Standard Pack
MP-1930	MP-1930 Battery Press Tool Kit without jaws	4.9	1set
	18V, 2.0 Ah Li-Ion Batteries	0.3	2pcs
ACCESSORIES	Charger	0.5	1pc
	Plastic case	1.7	1pc





#### **CZ-1550 Electric Powered Press Tool**

- Only 3S to finish one cycle press
- Press jaw with piston, to avoid maloperation
- Anti-slip handle and an optimized center of gravity for easier carry.





ELECTRIC POWERED PRESS TOOL

MULTI-LAYER COMPOSITE PIPE





STAINLESS STEEL PIPE







Specifica	tions				
Capacity:	up to 54mm Stainless s	teel pipe	Rated Power:	490V	l
	up to 108mm Plastic,M	ulti-layer composite and Copper pipes	Voltage:	AC22	20V 50/60HZ (or AC 110V 50/60H)
Output:	32kN			4.1kg	ıs(without jaw)
Stroke:	40mm		Tool Size:	456 >	81 x 130mm
Cycle time:	3S(DN25)		Hydraulic oil:	Shel	Tellus S2V HV15 130ml
Accessori	es:				
MODEL NO.		DESCRIPTION			Weight(kgs)
CZ-1550		CZ-1550 Press Tool Kit withou	t jaws		8.15
CZ-1550		Plastic case			3.2

#### HH-1550 **Electric Powered Press Tool**

520W High power 220V lasting power supply, Reliable and Stable

- Only 3S to finish one cycle press
- Press jaw with piston, to avoid maloperation.
- Anti-slip handle and an optimized center of gravity for easier carry.
- Motor drives, Micro-computer control system and double valve hydraulic system.





MULTI-LAYER COMPOSITE PIPE





PEX PIPE

STAINLESS STEEL PIPE



HH-1550





Specifications					
Capacity:	up to 54mm Stainless steel pipe	Rated Power:	520W		
	up to 108mm Plastic, Multi-layer composite and Copper pipes	Voltage:	AC220V 50/60HZ (or AC 110V 50/60HZ		
Output:	32kN	Service Interval:	10000cycles		
Stroke:	40mm	Weight:	4kgs(without jaw)		
Cycle time:	2.6-6S	Tool Size:	422×328×82mm		
		Hydraulic oil:	Shell Tellus S2V HV15 240ml		
HH-1550 F	ress Tool Kit				
MODEL NO.	DESCRIPTION		Weight(kgs)		

HH-1550 Press Tool Kit without jaws

Plastic case



HZ-1632

350° rotating head

With interchangeable dies





Technical data Press range: Ф16-32mm Rated press force: 60kN Rated work pressure: 63Mpa Stroke: 17mm 460mm Length: Weight: 3.3kgs Package: Metal box



Metal box

#### HZ-1550

#### Hand-operated Hydraulic Press Tool

Forged jaws with high strength, sturdy and durable

Stainless steel pipe Copper pipe Multi-layer composite pipe

• 350° rotating head

Package:

- Two stage hydraulic system with fast feed and power stroke
- Light weight due to high quality aluminum housing
- Automatic retraction when crimping is completed With safety valve to prevent pressure overload.

Technical data	
Press range:	12-54mm(1/2"-2") for stainless steel pipe
12-108mm(1/2"-	4") for PEX,Multi-layer and composite copper pipe
Rated press force:	32kN
Rated work pressure:	33Mpa
Stroke:	40mm



#### Hand-operated Hydraulic Press Tool

- 350° rotating head
- Two stage hydraulic system with fast feed and power stroke
- Light weight due to high quality aluminum housing
- Automatic retraction when crimping is completed
- With safety valve to prevent pressure overload.

Technical data	
Press range:	12-35mm Stainless steel pipe
	12-35mm(1/2"-1 3/8") Copper pipe
	16-40mm PEX&Multi-layer composite pipe
Rated pressure:	19kN
Stroke:	30mm
Oil capacity:	48ml
Tool size:	385x63.5x231mm
Weight:	1.6kg(without jaws)





For big size from 60~108mm stainless steel pipe

Technical data	
Press range:	60-108mm(2-4")for stainless steel pipe and copper pipe
Rated work pressure:	700bar(70MPa)
Stroke:	80mm
Oil capacity:	80ml
Tool size:	515x280x84mm
Weight:	9.3kgs(without jaw)
Package:	Metal box



FHT-3240 Hydraulic Press Head

- Forged jaws with high strength, sturdy and durable
- Hand pump,foot pump and electrical pump optional

Technical data	
Press range:	12-54mm(1/2"-2") for stainless steel pipe
12-108mm(1/2"-	-4") for PEX,Multi-layer composite and copper pipe
Rated press force:	32kN
Rated work pressure:	52Mpa
Stroke:	40mm
Package:	Metal box

42

HAND-OPERATED HYDRAULIC PRESS TOOL





### **EB-700**

#### **Battery Powered Hydraulic Pump**

- Lightweight and portable design for outdoor work
- OLED display show Pressure value, Maintenance note, Battery percentage, Working cycles ect.
- Automatic retraction when operation is complete
- Manual retract if need

PORTABLE LI-ION BATTERY POWERED HYDRAULIC PUMP

- Electronic sensor pressure control
- High performance 18V Li-ion battery
- Operates for crimping, cutting and punching heads
- All tools and hydraulic hose with couplers,easy and quick to connect













Comfort Backpack
















Specifications	
Oil Capacity:	Approx. 700ml
Pressure:	700bar(70Mpa)
Power:	490W
Voltage:	18.0V DC
Weight:	5.9kgs(with battery)
Tool size:	338x172x266mm
Battery:	5.0Ah Li-ion battery
Charging time:	100mins
Operation mode:	Remote control at 1.5 meters, or wireless remote control at 25 meters
Accessories	
Battery:	2pcs
Charger:	1рс
Stran.	1pc

Ensure safety operation









### MC-1228

#### **Cordless Tubing Cutter**

For Stainless steel pipe, Copper pipe and uncoated carbon steel pipe from Φ**12-28mm** 

- The light weight tool is only 2.9KGS,easy for one handed operation.
- Convenience and fast,9S cut off φ20 Stainless steel pipe.
- Without burr and iron dust, clean after cutting.
- Auto-adjust dia from 12mm to 28mm.

**CORDLESS TUBING CUTTER** 

- Build in LED light, to find the cutting position precisely.
- Easy to do pipe line maintenance in narrow space.













Specifications	
Cutting range:	<1.5mm ø12-28mm
Voltage/capacity	18V/2.0Ah
Charging Time	Approx.40mins
Charging Voltage	AC100V-240V; 50-60Hz
Weight	2.9kgs(with battery)
Cycle time	9s(ø20mm Stainless steel pipe)
Cyles/charger	150cyles(ø20mm Stainless steel pipe)
Tool Size	385x76x128mm

#### **ME-1225**

#### **Cordless Tube Expanding Tool**

**Quick & Easy Connections for PEX-a material** 

- Faster to connect PEX ring to PEX-a pipe
   Compact and portable, weight 2.45KGS with battery, easy for one handed operation
- More than 70 expensions per charge

#### **Expanding heads** Cycles of expansions

16x1.8/2.2 20x1.9/2.0 4-6 cycles 6-8 cycles 25x2.3 8-12 cycles 32x2.9 22-25cycles

#### Suit for various projects
















Auto-rotating head makes uniform expansion



**Expanding heads** 















European standard

Ф25x2.3mm Ф20x1.9/2.0mm Ф16x1.8/2.2mm





Specifications	
Max expanding dia. and wall thickness range:	<25X3.5mm,<32X2.9mm
Voltage/capacity:	18V/2.0Ah
Charging Time:	Approx.40mins
Charging Voltage:	AC100V-240V; 50-60Hz
Weight:	2.45kgs(with battery)
Tool Size:	193x94x270mm
Standard expanding heads:	16x1.8/2.2mm,20x1.9/2.0mm,25x2.3mm





## **BLM-1622 Battery Powered Axial Press Tool**

#### For A/C Lock sleeve connection

- Ergonomic design, with light weight, easily work overhead and in tight spaces
- The indicator light, with green indicating completion of press cycle, and red indicating press error or tool malfunction
- Brushless motor, with longer life time, more Run-time and maintenance-free
- Updated PCB technology, waterproof, dustproof, metal scraps proof
- Optional pressure sensor and wireless remote controller



BATTERY POWERED AXIAL PRESS TOO!



Specifications	
Output:	16kN
Stroke:	22mm
Suitable material:	Aluminum / Copper /Steel
Max connecting range:	Outer dia.16mm
Service interval:	10000cycles
Voltage of battery:	DC 18V,2.0Ah
Battery Charger:	AC 100V-240V 50-60Hz
Charging time:	Approx.40mins
Weight:	2.4kgs(with battery without jaw)
Tool size:	462x132x80mm
Accessories:	
Battery:	2pcs



Sealing ring of cylinder: Sealing ring of safety valve:

Charger:





## BLM-1240PE Battery Powered Axial Press & Expand Tool

Expanding dies:

For axial press & expand Pex and Multi-layer composite pipe

Specifications	
Output:	18kN
Stroke:	39mm
Expanding/Connecting range:	φ16-32mm
Service interval:	10000cycles
Voltage of battery:	DC 18V,2.0Ah
Connecting cycle time	Approx. 2.5-5S
Charging voltage:	AC 100V~240V ;50~60Hz
Charging time:	Approx.40mins
Weight:	3.7kgs
Tool size:	373x252x97mm
Accessories:	
Battery:	2pcs
Charger:	1pc
Sealing ring of cylinder:	1set
Sealing ring of safety valve:	1set
Connecting jaws: $\phi$ 16-20mm.	φ25-32mm



## **BLM-1240**Battery Powered Axial Press Tool

Pex pipe :φ16x2.2、φ20x2.8、φ25x3.5、φ32x4.4

PAP pipe(optional):φ16.2x2.6、φ20x2.9、φ25x3.7、φ32x4.7

For axial press Pex and Multi-layer composite pipe

	, , , , , ,
Specifications	
Output:	18kN
Stroke:	39mm
Connecting range:	ф16-32mm
Service interval:	10000cycles
Voltage of battery:	DC 18V,2.0Ah
Connecting cycle time	Approx. 2.5-5s
Charging voltage:	AC 100V~240V ;50~60Hz
Charging time:	Approx.40mins
Weight:	3.2kgs
Tool size:	362x216x80mm
Accessories:	
Battery:	2pcs
Charger:	1pc
Sealing ring of cylinder:	1set
Sealing ring of safety valve:	1set
Connecting jaws:	Ф16х2.2-20х2.8、Ф25х3.5-32х4





BATTERY POWERED AXIAL PRESS TOOL



## **BLM-2620**Battery Powered Axial Press Tool

For axial press air conditioner pipe Be used in air conditioner, heating, refrigeration system

Specifications	
Specifications	
Rated pressure:	26kN
Connecting range:	φ6.35-28.6mm copper pipe
Charging voltage:	AC 100V~240V ;50~60Hz
Charging time:	Approx.40mins
Oil capacity:	Approx.60ml
Stroke:	20mm
Service interval:	10000cycles
Voltage of battery:	DC 18V,2.0Ah
Ambient temperature:	-10°C~40°C
Weight:	3.2kgs(with battery with jaw)
Tool size:	358x130x80mm
Accessories:	
Connecting jaws(optional):	6.35、9.52、12.7、15.88、19.05、
	22.2、25.4、28.6mm (Integral type)
Battery:	2 pcs
Charger:	1 pc
Sealing ring of cylinder:	1 set
Sealing ring of safety valve:	1 set

## **BLM-4523**Battery Powered Axial Press Tool

For axial press air conditioner pipe Be used in air conditioner, heating, refrigeration system

Specifications	
Rated pressure:	45kN
Stroke:	23mm
Connecting range:	Φ6.35-38.1mm copper pipe
Oil capacity:	Approx.60ml
Ambient temperature:	-10°C~40°C
Service interval:	10000cycles
Voltage of battery:	DC 18V,2.0Ah
Charging voltage:	AC 100V~240V ;50~60Hz
Charging time:	Approx.40mins
Weight:	4.4kgs(with battery with jaw)
Tool size:	383x155x80mm
Accessories:	
Connecting jaws(optional):	6.35, 9.52, 12.7, 15.88, 19.05, 22.
	25.4, 28.6, 31.8, 34.9, 38.1mm
Battery:	2 pcs
Charger:	1 pc
Sealing ring of cylinder:	1 set
Sealing ring of safety valve:	1 set





## **SL-1622**Battery Powered Axial Press Tool

For A/C Lock sleeve connection

- Ergonomic design, with light weight, easily work overhead and in tight spaces
- The indicator light, with green indicating completion of press cycle, and red indicating press error or tool malfunction
- Only 2-4S to finish one cycle press
- SERVICE INTERVAL 10000 cycles



Output:	16kN
Stroke:	22mm
Suitable material:	Aluminum / Copper /Steel
Max connecting range:	Outer dia.16mm
Service interval:	10000cycles
Voltage of battery:	DC 18V,2.0Ah
Battery Charger:	AC 100V-240V 50-60Hz
Charging time:	Approx.40mins
Weight:	2.4kgs(with battery without jaw
Tool size:	463×132×76mm
Accessories:	
Battery:	2pcs
Charger:	1pc
Sealing ring of cylinder:	1set
Sealing ring of safety valve:	1set





 $oldsymbol{0}$ 





## SL-1240PE Battery Powered Axial Press & Expand Tool

For axial press & expand Pex and Multi-layer composite pipe

Output:	18kN	
Stroke:	39mm	
Expanding/Connecting range:	φ16-32mm	
Service interval:	10000cycles	
Voltage of battery:	DC 18V,2.0Ah	
Connecting cycle time	Approx. 2.5-5S	
Charging voltage:	AC 100V~240V ;50~60Hz	
Charging time:	Approx.40mins	
Weight:	3.7kgs	
Tool size:	373x252x97mm	
Accessories:		
Battery:	2pcs	
Charger:	1pc	
Sealing ring of cylinder:	1set	
Sealing ring of safety valve:	1set	
Connecting jaws: φ16-20mm、φ25-32mm		
Expanding dies:		
Pex pipe :φ16x2.2、φ20x2.8、φ25x3.5、φ32x4.4		



## SL-1240 Battery Powered Axial Press Tool For axial press Pex and Multi-layer composite pipe

Specifications  Output:	18kN
Stroke:	39mm
Connecting range:	ф16-32mm
Service interval:	10000cycles
Voltage of battery:	DC 18V,2.0Ah
Connecting cycle time	Approx. 2.5-5s
Charging voltage:	AC 100V~240V ;50~60Hz
Charging time:	Approx.40mins
Weight:	3.3kgs
Tool size:	372x229x76mm
Accessories:	
Battery:	2pcs
Charger:	1pc
Sealing ring of cylinder:	1set
Sealing ring of safety valve:	1set
Connecting jaws:	ф16x2.2-20x2.8、ф25x3.5-32x



#### SL-2620 Battery Powered Axial Press Tool

For axial press air conditioner pipe Be used in air conditioner, heating, refrigeration system

Specifications	
Rated pressure:	26kN
Connecting range:	φ6.35-28.6mm copper pipe
Charging voltage:	AC 100V~240V ;50~60Hz
Charging time:	Approx.40mins
Oil capacity:	Approx.35ml
Stroke:	20mm
Service interval:	10000cycles
Voltage of battery:	DC 18V,2.0Ah
Ambient temperature:	-10°C~40°C
Weight:	3.2kgs(with battery with jaw)
Tool size:	331x130x76mm
Accessories:	
Connecting jaws(optional):	6.35、9.52、12.7、15.88、19.05、
	22.2、25.4、28.6mm (Integral type)
Battery:	2 pcs
Charger:	1 pc
Sealing ring of cylinder:	1 set
Sealing ring of safety valve:	1 set



For axial press air conditioner pipe Be used in air conditioner, heating, refrigeration system

Rated pressure:	45kN
Stroke:	23mm
Connecting range:	Φ6.35-38.1mm copper pipe
Oil capacity:	Approx.35ml
Ambient temperature:	-10°C~40°C
Service interval:	10000cycles
Voltage of battery:	DC 18V,2.0Ah
Charging voltage:	AC 100V~240V ;50~60Hz
Charging time:	Approx.40mins
Weight:	4.4kgs(with battery with jaw)
Tool size:	347x155x76mm
Accessories:	
Connecting jaws(optional):	6.35, 9.52, 12.7, 15.88, 19.05, 22.
	25.4, 28.6, 31.8, 34.9, 38.1mm
Battery:	2 pcs
Charger:	1 pc
Sealing ring of cylinder:	1 set
Sealing ring of safety valve:	1 set







BATTERY POWERED AXIAL PRESS TOO!



### PZ-1240PE **Battery Powered Axial Press & Expand Tool**

Sealing ring of cylinder:

Expanding dies:

Connecting jaws:

54

Sealing ring of safety valve: 1set Connecting jaws: φ16-20mm、φ25-32mm

Pex pipe : $\phi$ 16x2.2、 $\phi$ 20x2.8、 $\phi$ 25x3.5、 $\phi$ 32x4.4

For axial press & expand Pex and Multi-layer composite pipe

or area process or expanse rost area rate tayor com-	
Specifications	
Output:	18kN
Stroke:	39mm
Expanding/Connecting range:	φ16-32mm
Service interval:	10000cycles
Voltage of battery:	DC 18V,2.0Ah
Connecting cycle time	Approx. 2.5-5S
Charging voltage:	AC 100V~240V ;50~60Hz
Charging time:	Approx.40mins
Weight:	3.7kgs
Tool size:	373x252x97mm
Accessories:	
Battery:	2pcs
Charger:	1nc

1set



#### PZ-1240 **Battery Powered Axial Press Tool** For axial press Pex and Multi-layer composite pipe

PAP pipe(optional): φ16.2x2.6、φ20x2.9、φ25x3.7、φ32x4.7

Specifications	
Output:	18kN
Stroke:	39mm
Connecting range:	ф16-32mm
Service interval:	10000cycles
Voltage of battery:	DC 18V,2.0Ah
Connecting cycle time	Approx. 2.5-5s
Charging voltage:	AC 100V~240V ;50~60Hz
Charging time:	Approx.40mins
Weight:	3.3kgs
Tool size:	372x229x76mm
Accessories:	
Battery:	2pcs
Charger:	1pc
Sealing ring of cylinder:	1set
Sealing ring of safety valve:	1set

ф16х2.2-20х2.8、ф25х3.5-32х4.4



#### **PZ-2620 Battery Powered Axial Press Tool**

For axial press air conditioner pipe Be used in air conditioner,heating,refrigeration system

Specifications		
Rated pressure:	26kN	
Connecting range:	φ6.35-28.6mm copper pipe	
Charging voltage:	AC 100V~240V ;50~60Hz	
Charging time:	Approx.40mins	
Oil capacity:	Approx.60ml	
Stroke:	20mm	
Service interval:	10000cycles	
Voltage of battery:	DC 18V,2.0Ah	
Ambient temperature:	-10°C~40°C	
	For axial press Pex and Multi-layer pipe	
Weight:	1.94kgs(tool with battery)	
Accessories:		
Connecting jaws(optional):	6.35、9.52、12.7、15.88、19.05、	
	22.2、25.4、28.6mm (Integral type)	
Battery:	2 pcs	
Charger:	1 pc	
Sealing ring of cylinder:	1 set	
Sealing ring of safety valve:	1 set	









#### PZ-4523 **Battery Powered Axial Press Tool**

For axial press air conditioner pipe Be used in air conditioner,heating,refrigeration system

Specifications	
Rated pressure:	45kN
Stroke:	23mm
Connecting range:	Φ6.35-38.1mm copper pipe
Oil capacity:	Approx.60ml
Ambient temperature:	-10°C~40°C
Service interval:	10000cycles
Voltage of battery:	DC 18V,2.0Ah
Charging voltage:	AC 100V~240V ;50~60Hz
Charging time:	Approx.40mins
Weight:	4.16kgs(tool with battery)
Tool size:	380x155x75mm
Accessories:	
Connecting jaws(optional):	6.35, 9.52, 12.7, 15.88, 19.05, 22.2,
	25.4, 28.6, 31.8, 34.9, 38.1mm
Battery:	2 pcs
Charger:	1 pc
Sealing ring of cylinder:	1 set
Sealing ring of safety valve:	1 set



Split type: 6.35, 9.52, 12.7, 15.88, 19.05, 22.2, 25.4mm
Integral type: 28.6, 31.8, 34.9, 38.1mm



Kit includes: PZ-4523 AXIAL PRESS TOOL, Connecting jaws, Two 2.0Ah Batteries, One Charger and Carrying Case.

MANUAL TOOL

56







#### HT-1240 Hand-operated Hydraulic Axial Press Tool

- Sliding connections for PEX and Multi-layer composite pipe
- Two stage hydraulic system with fast feed

Technical data		
Connecting/Expar	iding range:	φ16-32mm
Cutting range:		Max φ40mm
Stroke:		38mm
Oil capacity:		48ml
Package:		Plastic box
Accessorries:		
Connecting jaws:		φ16-20mm, φ25-32mm
Expanding dies:	Pex pipe :φ16x2.2-φ	20x2.8、φ25x3.5、φ32x4.4
	PAP pipe(optional) : $\phi$ 16.2x2.6、 $\phi$	20x2.9、φ25x3.7、φ32x4.7

#### Kit includes:

One axial press tool and expand tool, cutter

Two pairs connecting jaws, three expanding jaws and carrying case



#### FT-1240

#### Manual Axial Press Tool

- Sliding connections for PEX and Multi-layer composite pipe
- Connecting jaws made of alloy steel with precision casting, ratchet drive makes durable and reliable
- Connecting jaws built-in anti-attrition bushing makes easy sliding
   Expander handle made of high-strength aluminum alloy with precision forging, light and handy

Technical data	
Connecting/Expan	ding range: Φ16-32mm
Cutting range:	Max Φ40mm
Weight:	5.2kgs
Stroke:	40mm
Package:	Plastic box
Accessorries	
Connecting jaws:	φ16-20mm, φ25-32mm
Expanding dies:	Pex pipe :φ16x2.2-φ20x2.8、φ25x3.5、φ32x4.4
	PAP pipe(optional) :φ16.2x2.6、 φ20x2.9、 φ25x3.7、 φ32x4.7

One axial press tool and expand tool, cutter


Two pairs connecting jaws, three expanding jaws and carrying case



#### TE-1632 Manual Expand Tool

• Expander handle made of high-strength aluminum alloy with precision forging, light and handy.

Technical data	
Expanding range:	Ф16-32mm
Expanding dies:	Ф16-20,25,32mm
Length:	395mm
Weight:	1.33kgs
Expanding dies: Length:	Ф16-20,25,32mm 395mm



#### PE-1632 Manual Expand Tool

 Expander handle made of high-strength aluminum alloy with precision forging, light and handy.

Technical data	
Expanding range:	Ф16-32mm
Expanding dies:	Ф16,20,25,32mm
Length:	395mm
Weight:	2.12kgs



#### JT-1632 Manual Press Tool

- 360° rotating head
- Fast Change of crimping die without readjustment by specialfixing system
- With telescope handles, effort-saving

Technical data	
Press force:	40kN
Stroke:	16mm
Package:	Plastic box
Accessorries	
Press die for V type:	Ф12,15,18,22,28mm
Press die for U type:	Ф16,20,25,32mm
Press die for TH type:	Ф16,20,26,32mm

Note:The accessories type used at optional



ETM-20/ETM-32 Manual Expand Tool

Made of steel with precision casting

#### JT-1626 Manual Press Tool

- Ratchet locking type,ensure accurate reliability press
- Quick-change mounting for simple dies changing
   Antiskid handle structure designed make the press
- process more comforable

Technical data	
Weight:	2.1kgs
Length:	508mm
Package:	Plastic box
Accessorries:	
Press die for U type:	Φ16,20,25mm
Press die for TH type:	Φ16,20,26mm
Note The second of the term	

Note:The accessories type used at optional

#### FT-1225 Manual Axial Press Tool

- Easy changeable sliding jaws
- Smart tool body,easy one handed operation

Technical data	
Connecting range:	Φ12-25mm
Expanding range:	Ф12-20mm
Cutting range:	Max Φ42mm
Stroke:	80mm
Accessorries	
Jaws:	Φ12,16,20mm


Technical data Ф12-20mm ETM-20 Expanding range: ETM-20 Length: 160mm ETM-20 Weight: 0.33kgs ETM-32 Expanding range: Ф16-32mm ETM-32 Length: 180mm ETM-32 Weight: 0.58kgs

PATENT NO.:ZL 2004 3 0035588.1









Note:The accessories type used at optional



FT-15B

310mm

1.30kgs

Press range: Φ15(3/8") Φ18(1/2") Φ24(3/4")

Technical data

Length:

Weight:



FT-18B FT-24B

1.30kgs 1.30kgs


310mm

310mm

Paper box Paper box Paper box

ZT-1824	PEX Pipe Press Tool
Technical data	
Press range:	Ф18(1/2'')-Ф24(3/4'')
Length:	400mm
Weight:	1.20kgs
Package:	Paper box







U-25/32	PVC Pipe Cutter	
Technical data		
Model:	U <b>-</b> 25	U <b>-</b> 32
Max cutting range:	Ф25mm	Ф32mm
Length:	200mm	210mm
Weight:	0.14kgs	0.15kgs





- FT-1824 PEX Pipe Press Tool
- Stamping handle with heat treatment.Intensify,durable
- Comfortable skid resistance cover
- Alloy steel forged clamp arm is processed by CNC and strengthen by heat treatment, sturdy and durable

Technical data	
Press range:	Ф18(1/2'')-Ф24(3/4'')
Length:	290mm
Weight:	0.95kgs
Package:	Paper box



FT-1824B	PEX Pipe Press Tool

- Stamping handle with heat treatment.Intensify,durable and reliable
- Comfortable skid resistance cover
- Alloy steel forged clamp arm is processed by CNC and strengthen by heat treatment, sturdy and durable

Technical data	
Press range:	Ф18(1/2'')-Ф24(3/4'')
Length:	400mm
Weight:	1.60kgs
Package:	Paper box



FT-1530	PEX Pipe Press Tool		
Mechanical crimping tool for connecting fitting with pipe			

Crimp XPAP, PEX with fittings up to φ30mm

Package:

Technical data Φ15mm(3/8")-30mm(1") Press range: Φ15mm(3/8"),18mm(1/2"), Press dies: 20mm(5/8"),24mm(3/4"),30mm(1") Length: 400mm Weight: 1.6kgs



Technical data

Model

Length:

Weight:

PVC Pipe Cutter
Φ42mm
195mm
0.26kgs

1000	20
A.	

SSC-1530	PEX Pipe Cinch Tool
Technical data	
Cinching range:	3/8",1/2",5/8,",3/4",1"
Weight:	0.6kgs
Length:	278mm
Package:	Blister card

ST-1530	PEX Crimp Ring Removal Tool
Technical data	
Removal range:	Max up to 1"
Weight:	0.3kgs
Length:	220mm
Package:	Blister card

58 59

Plastic box











#### PS-1632B **Deburring Tool**

- Cutting device made of steel for long lifetime and with sharp cutting edge
- Large opening for removing pipe chips
- Anodic oxidation aluminium alloy sleeve is light and wear-resisting
- Hexagonal connector for changing different sizes easily, for handle, standard bit connectors or cordless screw driver








Technical data	
Features:	For multilayer composite and Pex pipe up to Φ32mm
Deburring range:	Ф16,20, 26,32mm











#### TB-22 Hydraulic Bending Tool

- For accurate one handed bending up to 90°, suit for 10-22mm[1/4"-7/8"] thickness below 1.0mm copper pipe
- Ideal in confined spaces
- Quick release and resetting of bending formers
- Bending formers easily changed
- Optimal bending results

Technical dat	a		
Former in inch		Former in metri	ic
Size	Weight	Size	Weight
1/4 "	0.093kgs	10mm	0.087kgs
5/16 "	0.091kgs	12mm	0.113kgs
3/8 "	0.08kgs	14mm	0.146kgs
1/2 "	0.128kgs	15mm	0.141kgs
5/8 "	0.153kgs	16mm	0.14kgs
3/4 "	0.194kgs	18mm	0.193kgs
7/8"	0.222kgs	20mm	0.18kgs
		22mm	0.201kgs

TBJ-32	Manual Danding Tool
IDJ-32	Manual Bending Tool

- For accurate one handed bending up to 90°, suit for copper and XPAP, PEX pipe
- Ideal in confined spaces
- Quick release and resetting of bending formers
- Bending formers easily changed
   Optimal bending results

Technical data			
Former in metric			
Size	Weight	Copper pipe	XPAP,PEX pipe
16mm	0.14kgs	√	√
20mm	0.18kgs	√	<b>√</b>
26mm	0.24kgs	×	<b>√</b>
32mm	0.42kgs	×	√



BJ-22	Manual Bending Tool
JJ EE	

- For accurate one handed bending up to 90°, suit for 10-22mm(1/4"-7/8") thickness below 1.5mm copper pipe
- Ideal in confined spaces
- Quick release and resetting of bending formers
- Bending formers easily changed
- Optimal bending results

Technical data	1		
Former in inch		Former in met	ric
Size	Weight	Size	Weight
1/4 "	0.093kgs	10mm	0.087kgs
5/16 "	0.091kgs	12mm	0.113kgs
3/8 "	0.08kgs	14mm	0.146kgs
1/2 "	0.128kgs	15mm	0.141kgs
5/8 "	0.153kgs	16mm	0.14kgs
3/4 "	0.194kgs	18mm	0.193kgs
7/8"	0.222kgs	20mm	0.18kgs
		22mm	0.201kgs





#### **ADVANTAGE OF ZUPPER PRESS JAW**

#### **Connecting Plate**

- Precision stamping
- Security design

**PRESS JAWS** 



#### Precision Forged Jaws

- Made by multi-axis CNC machine
- High strength, sturdy and durable

#### Special heat treatment process

Serial NO.

Tracking numbers easier to do

after-sales service

• Inspection control program to ensure long span life

ZUPPER TOOL have a wealth of design and practical experience, can provide customers with differentiated solutions according to customer needs, and to offer customers with pipe press technical support.

#### **SUITABLE PRESS TOOL**

- Compact series press jaws, suit for output 19kN press tool: PZ-1930,BZ-1930,SL-1930,MP-1930,BLM-1930,etc
- Another Compact series press jaws, suit for output 24kN press tool: PZ-2430,SL-2430,BLM-2430
- Standard series press jaws, suit for output 32kN press tool: PZ-1550,CZ-1550,EB-1550,ED-1550,BZ-1550,HH-1550,HZ-1550,FHT-3240,PZ-3240,etc
- Thicken series press jaws, suit for output 50kN press tool: ED-5050,HH-5050,PZ-5050,etc
- Big size press jaws, suit for output 80kN press tool: ED-60100,HH-60100, FHT-60100



Compact series press jaws



Standard series press jaws



Thicken series press jaws



Big size press jaws



Universal Jaw with interchangeable dies fit for PEX pipe Economic design for any need



Adaptor / Press Rings for 42-54mm

Interchangeable dies

- 1) One universal jaw with different types of dies, with a high cost performance
- 2) Quick change mounting for replace the dies easily

**NOTE:** The economic design only for PEX or PAP pipe, not for stainless pipe and copper pipes.



### THE NEW FLEXIBILITY-ANGLE JAWS Suit for narrow, angled installation areas which are difficult to access

#### **R8 Angle Jaw**

Provide with differentiated solutions according to customers requirment R8 M15, R8 M18, R8 M22, R8 M28, R8 M35 R8 V15, R8 V18, R8 V22, R8 V28, R8 V35......

#### **R8 Rotating Adaptor Jaw**

R8-19(suit for PZ-1930,SL-1930,BZ-1930, MP-1930,BLM-1930,etc) R8-24(suit for PZ-2430,SL-2430,BLM-2430)



R8 Angle Jaw



Spherical surface connection Swiveling 180-degree-flexibility

Precision stamping connecting plate Security design





#### **R9 Angle Jaw**

Provide with differentiated solutions according to customers requirment

R9 M15, R9 M18, R9 M22, R9 M28, R9 M35, R9 M42, R9 M54 R9 V15, R9 V18, R9 V22, R9 V28, R9 V35, R9 V42, R9 V54 13SR,20SR,25SR,30SR,40SR,50SR,60SR......







#### **R9 Rotating Adaptor Jaw**

R9-32(suit for PZ-3240,PZ-1550,CZ-1550,EB-1550, ED-1550, etc)



Spherical surface connection Swiveling 180-degree-flexibility

Precision stamping connecting plate Security design









Standard Series P	ress Jaws & Press	s Rings	
DESCRIPTION	JAW SIZE	Weight (KGS)	
	TH16	2.05	
	TH20	2.00	
	TH25	2.05	
	TH26	2.05	
	TH32	2.10	
PEX& MULTI-LAYER PIPE	TH40	2.2	
	TH50	1.9	
	TH63	2.67	

		(	
DESCRIPTION	JAW SIZE	Weight (KGS)	
	U16	1.95	
	U20	2.05	
	U25	2.00	
	U32	2.15	
	U40	2.20	
PEX& MULTI-LAYER PIPE	U50	2.8	
	U63	2.47	
	U75	2.6	

SV13 2.01  FOR STAINLESS STEEL SV20 2.07	
EOD STAINLESS STEEL SV20 2.07	
FOR STAINLESS STEEL 5-725	
PIPE SV25 2.03	
SV30 -	



Standard Series Pr	ess Jaws & Pres	s Rings	
DESCRIPTION	JAW SIZE	Weight (KGS)	
	VAU15	2.00	1578
	VAU20	2.06	
	VAU25	2.04	10/4
FOR COPPER PIPE	VAU32	2.09	
TORGOTTERTILE	VAU40	1.48	A 10
	VAU50	1.75	

Standard Series Pr	ess Jaws		
DESCRIPTION	JAW SIZE	Weight (KGS)	
FOR COPPER PIPE	VUS1/2"	2.00	
	VUS3/4"	2.10	An An
	VUS1"	2.05	
	VUS1-1/4"	2.08	
	VUS1-1/2"	2.70	
	VUS2"	3.90	

DESCRIPTION	JAW SIZE	Weight (KGS)	
	M12	2.00	
	M15	2.00	
	M18	1.95	
	M22	2.00	
	M28	2.00	
FOR STAINLESS STEEL	M35	2.05	
/COPPER PIPE	M42	1.35	
	M54	1.60	

PRESS JAWS





Standard Series Pr	ess Jaws		
DESCRIPTION	JAW SIZE	Weight (KGS)	
	V12	2.02	
	V15	1.95	A ANT A
	V18	2.10	
	V22	2.05	
	V28	2.00	
FOR STAINLESS STEEL	V35	2.05	
/COPPER PIPE	V42	1.40	
	V54	1.63	

	DESCRIPTION	JAW SIZE	Weight (KGS)	
		SDR13	2.0	
	FOR STAINLESS STEEL /COPPER PIPE	SDR20	2.1	
		SDR25	2.05	
		SDR30	1.25	0700
		SDR40	1.45	
		SDR50	1.6	
		SDR60	1.9	

Compact Series Press Jaws			
DESCRIPTION	JAW SIZE	Weight (KGS)	
	TH16	1.27	
	TH20	1.33	
PEX& MULTI-LAYER PIPE	TH25	1.41	
	TH26	1.35	
	TH32	1.40	



Compact Series Pre		
SCRIPTION	JAW SIZE	Weight (KGS)
(& MULTI-LAYER PIPE	U16	1.20
PEAR MULTI-LATER FIFE	U20	1.29
	U25	1.30
	U32	1.50
SCRIPTION	JAW SIZE	Weight (KGS)
	M12	1.23
	M15	1.30
R STAINLESS STEEL	M18	1.29
OPPER PIPE	M22	1.37
	M28	1.39
	M35	1.40
ESCRIPTION	JAW SIZE	Weight (KGS)
	V12	1 23

DESCRIPTION	JAW SIZE	Weight (KGS)
FOR STAINLESS STEEL /COPPER PIPE	V12	1.23
	V15	1.23
	V18	1.29
	V22	1.38
	V28	1.47



DESCRIPTION	JAW SIZE	Weight (KGS)
FOR STAINLESS STEEL PIPE	SV13	1.23
	SV20	1.27
	SV25	1.34
	SV30	-



DESCRIPTION	JAW SIZE	Weight (KGS)
	VAU15	1.23
FOR COPPER PIPE	VAU20	1.28
	VAU25	1.35
	VAU32	1.49



Special jaws can be made according to your requirements.

PRESS JAWS





Compact Series P	ress Jaws		
DESCRIPTION	JAW SIZE	Weight (KGS)	
	VUS1/2"	1.23	
FOR COPPER PIPE	VUS3/4"	1.26	
	VUS1"	1.48	



Big size Press Jaws				
DESCRIPTION	JAW SIZE	Weight (KGS)		
FOR STAINLESS STEEL		S63.5	3.05	30
	S76.1	3.7		
	S88.9	4.1		
PIPE	S101.6	5.5		
	S108	5.7		
	M67	3.5		
FOR STAINLESS STEEL	M76.1	3.9		
PIPE	M88.9	4.35		
	M108	5.7		
FOR STAINLESS STEEL PIPE	SDR80	4.4		
	SDR100	5.6		

_

PRESS JAWS